

Product:

Safety Data Sheet

ANNYS/ABS

Page: 1/6

Issue:1

Date: 2006-01-25

Invalidates and replaces the issue of:

PRODUCT LABELS

LABELLING (standard or EU):

Not applicable

TRANSPORT LABELLING:

Not applicable

1. Product and company identification

Commercial name:

ANNYS / ABS

Product application:

Oil for shock absorber

Company name:

TOTAL ISU OIL CO., LTD.

Address:

15F, YTN Tower 6-1 Namdaemunno 5-ga, Jung-Gu,

SEOUL, KOREA

Emergency number of the company:

82-2-6386-5151

Fax:

82-2-6386-5100

2. Composition/information on ingredients

PREPARATION:

Chemical nature:

Petroleum-derived severely refined mineral-base product

in which the polycyclic aromatic hydrocarbons (PCA or PAH) content, measured by IP 346, is

less than 3%

Subtances contributing to hazards:

None to our knowledge, in normal use

Impurities contributing to hazards:

None to our knowledge

3. Hazard identification

- Adverse human health effects:

Under normal conditions of use, the product holds no danger of intoxication

- Environmental effects:

Don't reject this product into the environment

- Physical and chemical hazards:

No specific risk of fire or explosion under normal conditions of use

4. First-aid measures

IN CASE OF SERIOUS MANIFESTATIONS, CALL IN A DOCTOR OR EMERGENCY MEDICAL CARE

Route of exposure:

- Inhalation:

Inhalation of heavy concentrations of vapour, fumes or spray, may cause mild irritation of the

Transport the person into fresh air, keep warm and allow to rest

- Contact with the skin:

If the skin is exposed to high-pressure spray, the product may enter the human organism. In all such cases the affected person must be taken to hospital, even if no sign of injury can be detected Immediately remove all soiled or stained clothing Wash the affected area immediately and repeatedly with soap and water.

X0/42184 0:213 MGPS

15F, YTN Tower, 6-1 Namdaemunno 5-ga, Jung-gu, SEOUL, KOREA

2007 3.



ANNYS/ABS Product: Issue:1

Page: 2/6

Date: 2006-01-25

Invalidates and replaces the issue of:

Keep eyes open and rinse immediately and repeatedly with water for at least 15 minutes - Contact with the eyes:

Possible risk of vomiting and diarrhea

Do not induce vomiting to avoid the risk of aspiration into the respiratory tract

Give nothing to drink

If the product is believed to have entered the lungs (in case of vomiting, for example), take the - Aspiration:

person to hospital for immediate care

5. Fire-fighting measures

Flash point:

- Ingestion:

See heading 9

Fire extinguishers:

- suitable :

- not suitable:

Foam, carbon dioxide (CO2), powder

do not use water jets (stick jets) for extinguishing fire since they could help to spread the flames.

Incomplete combustion and thermolysis produce toxic gases such as CO, CO2, various Specific hazards:

hydrocarbons, aldehydes and soot. These are highly dangerous if inhaled

An insulated breathing apparatus must be worn in confined premises with heavy concentrations of

fumes and gases

Accidental release measures

See also heading 8 and 13:

After spillage / leakage:

- on soil:

Firefighter protection:

Surfaces on which the product has been spilled may become slippery

Avoid discharge of the material in a stream or a sewer or cause ground contamination.

recovery by physical means

Contain and collect the spilled product with sand or any other inert material.

In the event of a major spill, inform the competent authorities if the situation cannot be brought

under control rapidly and efficiently

Use floating absorbent material to be removed mechanically - on water:

If the material has been discharged into a stream or a sewer, inform the authorities of the possible

presence of floating materials

Îf the material has been discharged into a stream or a sewer, inform the authorities

7. Handling and storage

HANDLING:

- Technical measures:

. prevention of user exposure:

Provide adequate ventilation in case of the potential formation of vapour, fumes, mist or spray Take all measures to reduce the risk of exposure, in particular to used or waste product

Keep away from flammable material; keep away from food and beverages

. Prevention of fire and explosion:

Empty containers may contain flammable or explosive vapours

There is a fire hazard associated with rags, paper or any other material used to remove spills which

become soaked with product

Avoid accumulate of these: they are to be disposed off safely after use



Issue:1

ANNYS/ABS Product:

Page:3/6

Date: 2006-01-25

Invalidates and replaces the issue of:

- Precautions :

Avoid static electricity build up with connection to earth,

Set up machinery and equipment so as to avoid the risk of accidental spills or splashes onto hot

machine parts and electrical contacts (on joint failure, for example)

Prevent oil leaks in pressure circuits resulting in a fine inflammable spray (the flammability limit

for oil mist is depressed when concentrations of about 45 g/m3 are reached)

Safe handling advice:

Avoid contact with strong oxidizing agents

Use only hydrocarbon-resistant containers, joints, pipes etc...

STORAGE:

- Technical measures:

Make the necessary arrangements and take all measures to prevent water and ground pollution

- Storage conditions:

. Suitable:

Store at room temperature, protected against contact with water and moisture, and away from any

source of ignition

Keep containers closed when not in use

. To be avoided:

Do not store exposed to the elements

- Incompatible products:

Dangerous reaction with strong oxidizing agents

- Packaging materials:

. Recommended:

Use only hydrocarbon-resistant containers, joints, pipes, etc.

Keep in original container if possible

Otherwise, transfer all indications on the regulatory label to the new container

8. Exposure controls / personal protection

Engineering measures:

Use the product in well-ventilated premises

When working on enclosed place (tanks, reservoirs...), make sure that atmosphere is not

suffocating and/or wear recommend equipment

- Control parameters:

. Occupational exposure limit:

. oil mist: 10mg/m3, for 15 minutes

. oil mist: 5mg/m3, for 8 hours

Personal protective equipment:

- Hand protection:

Impermeable hydrocarbon-proof gloves

recommended material: nitrile, neoprene

- Eye protection:

Goggles, in case of splashing

- Skin and body different hand protection:

As required, wear a face mask, hydrocarbon-proof clothing, and safety boots (when handling

drums)

Don't wear ring, watch or similar thing which will be able to hold the product and may give rise to

some skin diseases

Industrial hygiene:

Avoid prolonged and repeated contact with the skin, especially with used or waste product

Immediately remove all soiled or stained clothing.

If the product comes into contact with the skin, wash the affected area immediately and repeatedly

with soap and water

Use no abrasives, solvents or petroleum spirit

Do not use cloths stained with the product to dry hands

Don't put the product-soaked rags in the pockets of working clothes

9. Physical and chemical properties

Appearance:



ANNYS/ABS Product:

Page: 4/6

Date: 2006-01-25

Issue:1 Invalidates and replaces the issue of:

- Physical state:

Liquid

- Colour:

Yellow to amber

Odour:

Characteristic odour of oil

pH:

Not applicable

Specific temperatures of change in state

Flash point:

>= 140°C (ISO 2592)

Auto-ignition temperature:

> 250°C (ASTM E 659) This temperature may be significantly lower under particular conditions (oxidation on high surface

Explosion limits:

Not applicable

Density:

About 858kg/m3 at 15℃

Solubility:

- in water:

Insoluble and immiscible

- in organic solvents:

Soluble in many common solvents

- Viscosity:

Kinematic viscosity at 40℃: about 15 mm2/s

Log P n-octanol / water at 20°C:

mineral oil > 6

10. Stability and reactivity

Stability:

The product is stable under normal temperatures of storage, handling and use

Dangerous reactions:

Not dangerous reaction known under normal conditions of use, to refer to the technical notice

- Conditions to avoid:

Heat (temperatures above flash point), sparks, ignition points, flames, static electricity

- Materials to avoid:

Avoid contact with strong oxidizing

Dangerous decomposition products:

Incomplete combustion and thermolysis produce more or less toxic gases such as CO, CO2, various

hydrocarbons, aldehydes and soot

11. Toxicological information

ACUTE TOXICITY/LOCAL EFFECTS:

- Inhalation:

Risk is improbable under normal conditions of use

Inhalation of important concentration of vapour or aerosols may cause irritation of the upper

respiratory tract.

- Contact with the skin:

Risk is improbable under normal conditions of use

If the skin is exposed to high-pressure spray, the product may enter the human organism. In all such cases the affected person must be taken to hospital, even if no sign of injury can be detected

- Ingestion:

In case of ingestion of small quantities, no important effect observed, in case of ingestion of larger

amounts: abdominal pain, diarrhea, ...

SENSITIZATION:

To our knowledge, the product don't induce sensitization

CHRONIC TOXICITY OR LONG-TERM TOXICITY:

- Contact with the skin:

Characteristic skin affections (oil blisters) may develop following prolonged and repeated

exposure through contact with stained clothing



Page: 5/6 ANNYS/ABS Product: Date: 2006-01-25 Issue:1 Invalidates and replaces the issue of: The product is formulated from ingredients considered to be non-carcinogenic Carcinogenecity: 12. Ecological information Mobility: There is a slow loss by evaporation. - Air: Given its physical and chemical characteristics, the product generally shows little mobility in the - Ground: ground The product is insoluble; it spreads on the surface of the water - Water: Experimental data on the finished product are not available However, the "mineral oil" portion of the virgin product is intrinsically biodegradable. Particular Persistence and degradability: ingredients may not be biodegradable The virgin product is considered to present no danger for land-growing organisms. Ecotoxicity: It is considered to present a little danger for aquatic life. no information available for used product Experimental data on the finished product are not available 13. Disposal considerations Dispose in a safe manner in accordance with local/national regulations If need be, collection by an authorized waste contractor and regeneration or incineration in an approved installation Waste disposal: Conform to the regulation in effect Used packaging disposal: 13-01-06 (hydraulic oils containing only mineral oil) Industrial waste number EU: 14. Transport information Unregulated UN Number: Not restricted for transport, Road (ADR) / Rail (RID)/ River (ADNR): Not restricted for transport. Marine (IMO-IMDG): Not restricted for transport Airline (ICAO / IATA): 15. Regulatory information EUROPEAN REGULATIONS: - EC labelling: None - Symbol(s):

16. Other information

- R Phrase(s):

-SPhrase(s):

This data sheet conforms to standards defined by directives 91/155, 93/112/EEC & 2001/58/EC Data sheet required pursuant to Art.14 of directive 1999/45/EC.

Date of current version:

01/25/2006

None

None



Product:

ANNYS/ABS

Page: 6/6

Date: 2006-01-25

Issue:1

Invalidates and replaces the issue of:

Supersedes previous Safety Data Sheet of:

01/25/2006

"This Safety Data Sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and

accurate to the best of on knowledge at the date indicated hereabove.

It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk.

The information given herein in no way dispenses the user from knowing and applying all provisions regulating his or her activity. The user bears sole

liability for the precautions required when using the product.

The regulatory texts indicated herein are intended to aid the user to fulfill his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned."

End of document. Number of page(s): 6